

SSME EA/CIL
REDUNDANCY SCREEN

Component Group: Ducts and Lines
CIL Item: K216-01
Part Number: RS007369
Component: RIV Override Line
FMEA Item: K216
Failure Mode: Fails to contain oxidizer.

Prepared: D. Early
Approved: T. Nguyen
Approval Date: 7/25/00
Change #: 1
Directive #: CCBD ME3-01-5638

Page: 1 of 1

Phase	Failure / Effect Description	Criticality Hazard Reference
SMC 4.1	Oxidizer leakage into aft compartment. Overpressurization of aft compartment. Loss of vehicle. Redundancy Screens: SINGLE POINT FAILURE: N/A	1 ME-C3S, ME-C3M, ME-C3A,C

**SSME FMEA/CIL
DESIGN**

Component Group: Ducts and Lines
CIL Item: K216-01
Part Number: RS007369
Component: RIV Override Line
FMEA Item: K216
Failure Mode: Fails to contain oxidizer.

Prepared: D. Early
Approved: T. Nguyen
Approval Date: 7/25/00
Change #: 1
Directive #: CCBD ME3-01-5638

Page: 1 of 1

Design / Document Reference

FAILURE CAUSE: A: Parent material failure or weld failure.

THE LINE ASSEMBLY (1) IS MANUFACTURED UTILIZING 321 CRES TUBE AND INCONEL 625 BAR. 321 CRES TUBING WAS SELECTED BECAUSE OF ITS STRENGTH, FABRICABILITY, GENERAL CORROSION RESISTANCE, AND STRESS CORROSION RESISTANCE (2). INCONEL 625 WAS SELECTED FOR ITS WELDABILITY, FORMABILITY, RESISTANCE TO STRESS CORROSION CRACKING, AND CORROSION RESISTANCE (2). INCONEL 625 POSSESSES THE REQUIRED STRENGTH WITHOUT REQUIRING HEAT TREAT. ALL MATERIALS USED IN THE LINE FABRICATION ARE LOX COMPATIBLE (2). FLANGE AND ELBOW SECTIONS INCORPORATE RADIUS JOINTS TO REDUCE STRESS CONCENTRATIONS. OFFSET LIMIT REQUIREMENTS ARE ESTABLISHED TO REDUCE STRESS CONCENTRATIONS AND IMPROVE WELD GEOMETRY. TUBING STOCK IS DRAWN TO MAINTAIN SURFACE REGULARITY. INSTALLATION IS CONTROLLED FOR ANGULARITY AND OFFSET PER SPECIFICATION REQUIREMENTS (3). MINIMUM FACTORS OF SAFETY FOR THE LINE MEET CEI REQUIREMENTS (4). HIGH AND LOW CYCLE FATIGUE LIFE MEET CEI REQUIREMENTS (5). THE LINE ASSEMBLY HAS COMPLETED PRESSURE CYCLING AND ULTIMATE PRESSURE DVS TESTING (6). THE LINE ASSEMBLY PARENT MATERIALS WERE CLEARED FOR FRACTURE MECHANICS/NDE FLAW GROWTH, SINCE THEY ARE NOT FRACTURE CRITICAL PARTS (7). TABLE K216 LISTS ALL THE FMEA/CIL WELDS AND IDENTIFIES THOSE WELDS IN WHICH THE CRITICAL INITIAL FLAW SIZE IS NOT DETECTABLE, AND THOSE WELDS IN WHICH THE ROOT SIDE IS NOT ACCESSIBLE FOR INSPECTION. THESE WELDS HAVE BEEN ASSESSED AS ACCEPTABLE FOR FLIGHT BY RISK ASSESSMENT (8).

(1) RS007369; (2) RSS-8582, RSS-8575; (3) RA1102-006; (4) RSS-8546, CP320R0003B; (5) RL00532, CP320R0003B; (6) SSME-80-1466; (7) NASA TASK 117; (8) RSS-8756

**SSME FM CIL
INSPECTION AND TEST**

Component Group: Ducts and Lines
 CIL Item: K216-01
 Part Number: RS007369
 Component: RIV Override Line
 FMEA Item: K216
 Failure Mode: Fails to contain oxidizer.

Prepared: D. Early
 Approved: T. Nguyen
 Approval Date: 7/25/00
 Change #: 1
 Directive #: CCBD ME3-01-5638

Page: 1 of 1

Failure Causes	Significant Characteristics	Inspection(s) / Test(s)	Document Reference
A	LINE FLANGE ELBOW		RS007369 RS007147 RS007237
	MATERIAL INTEGRITY	MATERIAL INTEGRITY IS VERIFIED PER DRAWING REQUIREMENTS.	RS007369 RS007147 RS007237
		DETAILS ARE PENETRANT INSPECTED PER SPECIFICATION REQUIREMENTS.	RA0115-116
	WELD INTEGRITY	ALL WELDS ARE INSPECTED TO DRAWING AND SPECIFICATION REQUIREMENTS PER WELD CLASS. INSPECTIONS INCLUDE: VISUAL, DIMENSIONAL, PENETRANT, RADIOGRAPHIC, ULTRASONIC, AND FILLER MATERIAL, AS APPLICABLE.	RL10011 RA0607-094 RA0115-116 RA0115-006 RA1115-001 RA0115-127
	ASSEMBLY INTEGRITY	THE ASSEMBLY IS PROOF PRESSURE TESTED PER DRAWING REQUIREMENTS. WELDS ARE PENETRANT INSPECTED AFTER PROOF PRESSURE TEST PER SPECIFICATION REQUIREMENTS.	RS007369 RA0115-116
	FLIGHT FLOW TESTING	THE EXTERNAL SURFACE IS VISUALLY INSPECTED PRIOR TO EACH LAUNCH. (LAST TEST)	OMRSD V41BU0.030

Failure History: Comprehensive failure history data is maintained in the Problem Reporting database (PRAMS/PRACA)
 Reference: NASA letter SA21/88/308 and Rocketdyne letter 88RC09761.
 Operational Use: Not Applicable.

SSME FMEA/CIL
WELD JOINTS

Component Group: Ducts and Lines
CIL Item: K216
Part Number: RS007369
Component: RIV Override Line
FMEA Item: K216

Prepared: D. Early
Approved: T. Nguyen
Approval Date: 7/25/00
Change #: 1
Directive #: CCBd ME3-01-5638
Page: 1 of 1

Component	Basic Part Number	Weld Number	Weld Type	Class	Root Side Not Access	Critical Initial Flaw Size Not Detectable		Comments
						HCF	LCF	
LINE	RS007369	1-3	GTAW	I	X	X		
