Failure Modes and Effects Analysis/Critical Items List

Document Number: JSC-38378 Document Rev. No.: C Document Date: 8/26/97

Title: Risk Assessment Executive Summary Report (RAESR) for the USA SAFER

Item Name: Hand Controller Module (HCM) Qty: 1 FMEA Number: US-SFR-300

Grip

Item Part Number: SED33106098 ORU Name: SAFER

Subsystem Name: HCM ORU Part Number: SED33105900-311

Function: Converts mechanical motion into electrical commands in order to control electronic logic.

Item Type Designator: C PG/IP Identifier: N/A

Reference Designator/Find No.: N/A Drawing Number: SED33106098

Logistics Control Number: N/A

End Item Name: SAFER

End Item Capability: Six degrees of freedom through 24 thrusters, each rated at 0.8 ± 0.08 lbs. force in vacuum.

End Item Function: Provides emergency EVA self-rescue for separated crewmember.

ISS Zone: EVA Shuttle Zone: EVA

Criticality

Critical Item: Yes: No: X Criticality Category: 1R 1R/3

Success Paths Remaining:

Paths:

Failure (Mode, Cause, Detection, Corrective Action)

Failure Mode: Hand Controller Module (HCM) Grip fails to initiate thruster command.

Failure Mode Code:

Failure Cause: Switch Failure, EEE part failure, short/open circuit, contamination, software error, radiation event, EMI.

Failure Detection:

Flight: IVA – IVA checkout.

EVA – No commanded motion. Thruster LED does not illuminate.

Ground: Functional Test.

Time To Detect Quantity: 10 Time To Detect Units: Seconds

Correcting Action: IVA – If the IVA checkout detects a failure, the backup SAFER (if available) will be used.

EVA - Cycle power. If not successful, no other corrective action.

Remarks: None

Failure Effect Phase: EVA Operations Affected Stage(S): EVA Operations

Failure Effect

On ORU/Assembly:

<u>First/Second Failure:</u> Inadvertent EVA crewmember separation.

Third (this) Failure: No commanded motion.

On Subsystem/Next Assembly: None.

On End Item/Segment: Prevents self rescue.

On Crew/ISS: Possible loss of EVA crewmember.

Time To Effect Quantity: 1 Time To Effect Units: Minutes

Redundancy Screen

ISS (Shuttle)

Checkout Pre-Launch (A): Pass Checkout On-Orbit (B): N/A

Detection Flight Crew: Pass Or Detection Ground Crew: Fail

Loss Of Redundancy

From A Single Cause (C): N/A